



## SPECIFICATIONS:

<b>Electrical:</b>	
Frequency range	1000 – 3000 MHz
VSWR	< 2:1
Nominal input impedance	50 Ω
Radiation pattern	Monopole, omni-directional in azimuth
Connector	7/16 female
Feed power handling	250 W
Gain on horizon	0 dBi typical, 5 dBi minimum
Polarisation	Linear (vertical polarised only)
<b>Mechanical:</b>	
Dimensions (d x h)	150 mm x 170 mm
Total mass	0.5 kg
Mounting method	NATO flange 4 and 6 holes
Ground plane requirement	Flat on vehicle top, 1 m <sup>2</sup> clear area
<b>Environmental:</b>	
Wind survival on vehicle	160 km/h
Temperature range	-10 °C to +55 °C
Water and dust resistance	IP 67

## PRODUCT FEATURES:

- Wide bandwidth covered in a single antenna
- Low VSWR, high gain over the band
- 250 W feed power handling
- Passive construction
- Full gain antenna, no lossy components used for matching

## APPLICATIONS:

- Wideband monitoring and jamming

The antenna can be customised if required, for different frequency ranges or greater power handling.

## PRODUCT DESCRIPTION:

This wideband high-power transmit antenna is designed for full-coverage jamming from 1000 to 3000 MHz. Housed in a small, rugged radome, the antenna is mounted on a vehicle roof or elevated ground plane.

The antenna element inside has excellent gain and VSWR over the full-band. No lossy matching network is used, the antenna structure is designed to work over the full frequency range, giving maximum radiation, and allowing high transmitter powers to be used.

The antenna can be used for reception at lower frequencies with reasonable gain.