



T-10 Series CW TWT Microwave Power Amplifiers
4.0 – 18.0 GHz • 10Watts, Minimum Rated Power

Instruments for Industry, T-10 Series Amplifiers provide outstanding RF performance. Our "T-10 Series" products are a mature design but incorporate the latest features with respect to control and monitoring. These amplifiers are "State of the Art"; have field proven reliability and unsurpassed performance as the best in the industry. These products are available in a wide range of frequency bands from 4.0GHz-18.0GHz at 10 watts.

Operation safety and ease of use are paramount in IFI product designs. The IFI T-10 Series include a full complement of RF and hardware protection systems including high VSWR, over-current and voltage protection as well as redundant thermal and airflow sensors to prevent the TWT from overheating. In addition, the T-10 series includes a state-of-the-art interface that is sophisticated, comprehensive, but yet simple to use. Our amplifiers feature modular construction and this concept of modular design minimizes internally produced EMI signal leakage and provides easy access for field service and rapid turnaround at depot level repair facilities.

The backlit LCD screen shows forward/reverse power indication, system status and self-diagnostic information. All the amplifier operating parameters are simultaneously available in the amplifier front panel display as well as over the remote bus. Selection switches allow you to switch the amplifier to the desired mode of operation for local control if the unit is not being operated remotely.

For computer automation both an RS-232 and IEEE-488 interface are included. To meet individual application needs, the

T-10 Series amplifiers can be easily customized with harmonic filters or other options. With this capability and its reliable elegant design, the T-10 series amplifiers are the perfect amplifier for your microwave needs. IFI offers different size packages and configurations to best suit your application. A product and design built to last!

IFI RF Power Amplifier Features:

- Instantaneous Broadband Frequency range
Modular Design Construction
Rugged Construction & High Reliability
Backlit LCD Display
Integrated Force Air Cooling
Self-diagnostic circuitry
IEEE-488 interface, RS232
Solid State Power Supply



Models & General Specifications:

Table with 8 columns: Model Number, Frequency Range (GHz), Rated Power (watts minimum), P1dB Power (nominal), Gain (dB min), Mains (kVA), Weight (Pounds), Size (Inches). Rows include models T84-10, T104-10, T106-10, T128-10, T1812-10, T184-10, T186-10, and T188-10.



T-10 Series CW TWT Microwave Power Amplifiers

4.0 – 18.0 GHz • 10Watts, Minimum Rated Power

Standard Features for IFI T-10 Series TWT Amplifiers

Table with 2 columns: Standard Features and Description. Features include VSWR protection, remote control, RF ports, and diagnostics.

Specifications:

Table with 2 columns: Specification and Value. Includes frequency range, power, gain, impedance, connectors, VSWR, temperature, humidity, altitude, cooling, modulation, configuration, and spurious outputs.

Standard Prime Powers:

Table listing standard prime powers: 100, 115, 120 VAC; 200, 220, 230, 240VAC; and 100/200VAC, 115/208 or 200/220/230/240VAC.

Some Available Options for IFI T-10 Series TWT Amplifiers

Table listing options: Option 103 G/D (Graceful Degradation), Option 110-1E (Remote Control), Option 110-2 (Remote Control), Option 110-3 (Remote Control), Option 113 (Chassis Slides), Option 118F or R (RF Connections), Option 123F or R (Reflected RF Sample Port).



Instruments For Industry

The Power Of Choice

CW TWT

AMPLIFIERS

T-10 Series CW TWT Microwave Power Amplifiers

4.0 – 18.0 GHz • 10Watts, Minimum Rated Power

Option 129E:	External Harmonic Filtering
Option 129S:	Internal Switchable Harmonic Filtering

Instruments For Industry

903 South Second Street • Ronkonkoma, NY 11779 • 631-467-8400 • 631-467-8558 • sales@ifi.com • www.ifi.com



T-10 Series CW TWT Microwave Power Amplifiers

4.0 – 18.0 GHz • 10Watts, Minimum Rated Power

Outline Configurations:

5.25" High Chassis Outline

